1997 EDITORIAL INDEX

◀ CAREER CONCERNS ▶

• World Wide Web carries courses to further RF education (March, p. 202)
• Thorough preparation is essential when relocating (May, p. 276)

◀ COMMERCIAL ▶

• Wireless semiconductor markets are poised for growth (February, p. 31)
• Wireless technology expands into new roles (March, p. 30)
• Information needs drive communications services (April, p. 32)
• ITS technology drives future highway infrastructure (May, p. 41)
• Aerospace industry begins slow climb (June, p. 38)
• Leading component supplier earns ISO 9001 certification (June, p. 42)
• Distributor's capabilities fill customers' requirements (June Cover, p. 121)
• CATV industry challenges RF designers (July, p. 28)
• Military/commercial programs offer dual personalities (September, p. 31)
• Wireless industry fortunes continue to multiply (December, p. 57)

◀ COMMUNICATIONS ▶

• Technology helps secure role of personal communications (May, p. 45)

◀ COMPONENTS ▶

• Understand the operation of channelized active filters (January, p. 89)
• Single loop locks low-noise frequency sources (January, p. 126)
• Miniature VCOs cut current in portable designs (January, p. 128)
• Innovative DR-based filters cut spurious levels (January, p. 139)
• Oscillator design delivers thermal stability at Ka-Band (February, p. 81)
• Accurately model SAW filter behavior (February, p. 85)
• ADCs and DACs send signals between realms (February, p. 103)
• Driver amplifier provides wide gain-control range (February, p. 140)
• Power dividers provide rejection without filters (February, p. 146)
• MMIC techniques yield tiny couplers and power dividers (February, p. 152)
• Synthesis formulas simplify coplanar-waveguide design (March, p. 84)
• Construct a PCS base-station push-pull amplifier (March, p. 148)
• Broadband limiters protect microwave test equipment (March, p. 201)
• Smart antennas enhance cellular/PCS performance, Part 1 (April, p. 76)
• Use rectangular waveguide for highpass filters (April, p. 88)
• Determine actual S-parameter values in generalized impedances (April, p. 92)
• Surface-mount capacitors craft 900-MHz oscillator (April, p. 102)
• DSP enhances base-station performance (April, p. 155)
• New antenna designs keep a low profile (May, p. 31)
• Design techniques govern flexible-waveguide performance (May, p. 155)
• Smart antennas enhance cellular/PCS performance, Part 2 (May, p. 164)
• Laser sheds light on antenna range alignments (May, p. 224)
• Miniature PLLs fit surface-mount packs (May, p. 230)
• Compact DF antenna delivers high AOA accuracy (June, p. 61)
• High-performance CPW filters use bond wires (June, p. 89)
• Equations model transmission-line transformers (June, p. 94)
• Low-noise amplifiers boost fiber-optic data systems (June, p. 130)
• LDMOS amplifier drives IRIDIUM system testing (June, p. 134)
• Feedforward techniques spawn cellular power amps (June, p. 144)
• Phase-locked YIGs offer 13-to-15-GHz fixed outputs (June, p. 146)
• Use peak factor to characterize power amplifiers (July, p. 54)
• Bias tee delivers high-power, wide-bandwidth operation (July, p. 66)
• Technique provides burst control in GSM power amplifiers (July,

1997 EDITORIAL INDEX

◀ CAREER CONCERNS ▶

• World Wide Web carries courses to further RF education (March, p. 202)
• Thorough preparation is essential when relocating (May, p. 276)

◀ COMMERCIAL ▶

• Wireless semiconductor markets are poised for growth (February, p. 31)
• Wireless technology expands into new roles (March, p. 30)
• Information needs drive communications services (April, p. 32)
• ITS technology drives future highway infrastructure (May, p. 41)
• Aerospace industry begins slow climb (June, p. 38)
• Leading component supplier earns ISO 9001 certification (June, p. 42)
• Distributor's capabilities fill customers' requirements (June Cover, p. 121)
• CATV industry challenges RF designers (July, p. 28)
• Military/commercial programs offer dual personalities (September, p. 31)
• Wireless industry fortunes continue to multiply (December, p. 57)

◀ COMMUNICATIONS ▶

• Technology helps secure role of personal communications (May, p. 45)

◀ COMPONENTS ▶

• Understand the operation of channelized active filters (January, p. 89)
• Single loop locks low-noise frequency sources (January, p. 126)
• Miniature VCOs cut current in portable designs (January, p. 128)
• Innovative DR-based filters cut spurious levels (January, p. 139)
• Oscillator design delivers thermal stability at Ka-Band (February, p. 81)
• Accurately model SAW filter behavior (February, p. 85)
• ADCs and DACs send signals between realms (February, p. 103)
• Driver amplifier provides wide gain-control range (February, p. 140)
• Power dividers provide rejection without filters (February, p. 146)
• MMIC techniques yield tiny couplers and power dividers (February, p. 152)
• Synthesis formulas simplify coplanar-waveguide design (March, p. 84)
• Construct a PCS base-station push-pull amplifier (March, p. 148)
• Broadband limiters protect microwave test equipment (March, p. 201)
• Smart antennas enhance cellular/PCS performance, Part 1 (April, p. 76)
• Use rectangular waveguide for highpass filters (April, p. 88)
• Determine actual S-parameter values in generalized impedances (April, p. 92)
• Surface-mount capacitors craft 900-MHz oscillator (April, p. 102)
• DSP enhances base-station performance (April, p. 155)
• New antenna designs keep a low profile (May, p. 31)
• Design techniques govern flexible-waveguide performance (May, p. 155)
• Smart antennas enhance cellular/PCS performance, Part 2 (May, p. 164)
• Laser sheds light on antenna range alignments (May, p. 224)
• Miniature PLLs fit surface-mount packs (May, p. 230)
• Compact DF antenna delivers high AOA accuracy (June, p. 61)
• High-performance CPW filters use bond wires (June, p. 89)
• Equations model transmission-line transformers (June, p. 94)
• Low-noise amplifiers boost fiber-optic data systems (June, p. 130)
• LDMOS amplifier drives IRIDIUM system testing (June, p. 134)
• Feedforward techniques spawn cellular power amps (June, p. 144)
• Phase-locked YIGs offer 13-to-15-GHz fixed outputs (June, p. 146)
• Use peak factor to characterize power amplifiers (July, p. 54)
• Bias tee delivers high-power, wide-bandwidth operation (July, p. 66)
• Technique provides burst control in GSM power amplifiers (July,

p. 70)
• Optimize microwave-circuit performance with microwave tuners (July, p. 80)
• Low-profile mixers flatten PCB designs (July Cover, p. 102)
• Linear amplifiers target PCS and WLL base stations (July, p. 110)
• Power amplifiers serve diverse system applications (July, p. 118)
• Evaluate 1/f effects on oscillator phase noise (August, p. 82)
• Assessing distortion at microwave interface junctions (August, p. 108)
• Examine the effects of aliasing on non-symmetric filters (August, p. 118)
• Cooled filter/LNA assembly enhances cellular coverage (August Cover, p. 172)
• MMIC amplifier attains 12-dB gain at 155 GHz (August, p. 182)
• Interdigital design forms low-cost bandpass filters, Part 1 (September, p. 77)
• Antenna design offers small size with wide bandwidth (September, p. 105)
• Mixed-signal chip set targets HFC cable networks (September Cover, p. 169)
• Tunable CDMA combiners add cellular/PCS capacity (September, p. 181)
• GaAs MMIC amplifier drives WLAN applications (September, p. 184)
• Firm resurrects low-noise-amplifier line (September, p. 186)
• DSP core brings new power to communications systems (September, p. 188)
• High-speed ADC acquires 100 MSamples/s and 230 MHz (September, p. 190)
• Dual-band downconverter IC aims at TDMA handsets (October, p. 34)
• Thermal modeling aids the design of packaged amplifiers (October, p. 64)
• Interdigital design forms low-cost bandpass filters, Part 2 (October, p. 79)
• Use Allan Variance to characterize oscillator stability (October, p. 92)
• Wilkinson-Divider design provides reduced size (October, p. 104)
• Amplifiers power dual-band handsets (October, p. 113)
• Compact amplifiers and mixers score high linearity (October, p. 148)
• Machine automatically cuts/strips coaxial cables (October, p. 168)
• Components and assemblies serve millimeter-wave systems (October, p. 170)
• Analysis method characterizes microwave oscillators, Part 1 (November, p. 82)
• Power amplifiers drive cellular/PCS systems (November, p. 150)
• Efficient power amplifier boosts 2.4 to 2.5 GHz (November, p. 152)
• Design techniques enhance isolation in switch assemblies (December, p. 110)
• Analysis method characterizes microwave oscillators, Part 2 (December, p. 125)
• Adaptive antenna technology aids wireless transmission (December, p. 139)
• Design method produces direct-coupled DR filters (December, p. 147)
• Approach simplifies the construction of microstrip splitters (December, p. 161)
• Tuning elements adjust high-frequency circuits (December, p. 165)
• Amplifiers add power to firm's offerings (December, p. 242)
• Amplifiers boost company's reputation (December, p. 248)
• Miniature package holds oven-controlled oscillators (December, p. 250)
• Cellular divider/combiner switches with low loss (December, p. 263)
• Comparing calibration kits for subminiature connectors (December, p. 268)

◀ COMPUTER-AIDED ENGINEERING ▶

• Use EM software for component optimization, Part 2 (January, p. 65)
• Evaluate RF designs with an EM simulator (January, p. 123)
• Selecting optimum simulation tools for RF IC design (February, p. 91)
• Three-dimensional modeling software speeds EM solutions (February Cover, p. 112)
• EM simulator benefits from enhanced features (February, p. 126)
• Software transforms design schematics to useful layouts (February, p. 144)
• Mathematical modeling program receives major upgrade (March, p. 190)
• Flexible program furthers analysis of spreadsheet files (March, p. 198)
• Use SPICE models to simulate quartz-crystal oscillators (April, p. 70)
• Innovative simulator models silicon upconverter RF IC, Part 2 (April, p. 106)
• Program evaluates cascaded receiver signal chains (April, p. 151)
• Software suite helps manage process flow (April, p. 156)
• Low-cost analysis program supports scientific graphics (April, p. 161)
• Transmission-line model simulates microstrip radiators (May, p. 171)
• CAE software aids design of L-band MMIC LNA (May, p. 177)
• Software provides signal-path solutions (June, p. 107)
• Program helps compute capacitor parameters (June, p. 111)
• Software models satellite links (June, p. 112)
• Software tackles multilayer PCB designs (June, p. 114)
• WLAN standard paves the way for mobile networking (August, p. 46)
• Derive IM effects from solid-state device physics (August, p. 96)
• CAE program models conformal antennas (August, p. 186)
• Microwave CAD tools simplify the design of VCOs (September, p. 96)

• Retracing key moments in the life of Maxwell (November, p. 35)
• SPICE tools provide behavioral modeling of PLLs (November, p. 71)
• Integrate CAD methods for accurate RF IC simulation (November, p. 88)
• The FIT approach enhances EM simulation capability (November, p. 102)
• CD/SS methods offer cost-effective CDMA option (November, p. 117)
• EM tools enhance simulation accuracy (November, p. 133)
• EM simulator analyzes complex circuit behavior (November, p. 146)
• Software simulates thermal duty cycles (November, p. 149)
• Simulator fosters analog and digital designs (December, p. 202)
• Low-cost design suite rivals high-end products (December, p. 206)
• Design suite revolves around EM simulator (December, p. 210)
• Software models MESFETs and HEMTs (December, p. 214)
• Program delivers presentation graphics (December, p. 218)

◀ CONFERENCES ▶

• Analog and digital technologies mature at Fifth WIRELESS Symposium (March, p. 55)
• Latest products reveal trends in wireless design (March, p. 63)
• 1997 International Microwave Symposium (May, p. 60)
• Products ease design pressures (May, p. 120)
• European Conference canvasses military and commercial areas (July, p. 38)
• Four days of educational workshops (July, p. 88)
• Program to highlight advances in European technology (August, p. 152)
• Exhibition offers latest European products (August, p. 162)
• GaAs and Si advance at the 43rd annual IEDM (October, p. 30)
• WIRELESS/Portable Conference updates technology progress (November, p. 52)
• Latest products unveiled at European exhibition (December, p. 32)
• Technical program highlights wireless applications (December, p. 73)
• Products fuel a growing wireless market (December, p. 99)

◀ CROSSTALK ▶

• Martin Cooper, chairman of ArrayComm, Inc. (March, p. 39)
• Ulrich Rohde, executive vice president of Strategic Planning at Ansoft Corp. (July, p. 40)
• Tom Leonard, CEO of Alpha Industries (September, p. 51)
• Masumi Fukuta, President of Fujitsu Quantum Devices Ltd. (October, p. 49)

◀ DEFENSE ELECTRONICS ▶

• Military industry undergoes a revolution (June, p. 29)
• High-speed synthesizers benefit radar/EW systems (June, p. 136)
• Tactical VHF radio secures 64-kb/s data rates (June, p. 140)
• Digital battlefield drives military technology (September, p. 47)

◀ DEVICES & ICs ▶

• Technique provides measurement of HBT thermal resistance (February, p. 55)
• PHEMT devices offer high power density and efficiency (February, p. 61)
• Achieve microwave frequency conversion with cold FETs (February, p. 73)
• Chip sets simplify DECT handset and base-station design (February, p. 132)
• Wireless technology expands into new roles (March, p. 30)
• Silicon upconverter RF IC simplifies cable modem designs, Part 1 (March, p. 136)
• Direct-conversion receiver IC simplifies DBS set-top boxes (March Cover, p. 169)
• Semiconductors serve high-frequency commercial systems (April, p. 139)
• Digital design improves radar pulse compression (May, p. 135)
• Custom varactor diode eliminates inductors in VCXO designs (May, p. 187)
• Receiver IC buttresses spread-spectrum systems (May, p. 215)
• SMT trimmer capacitors feature tiny footprint (May, p. 228)
• Downconverter IC processes signals from 500 to 1900 MHz (July, p. 134)
• Single ASIC assists cable-modem designers (July, p. 146)
• Pair of ICs simplify design of GPS receivers (August, p. 180)
• Baseband processors employ CD/SS techniques (October, p. 152)
• Power transistor optimized for CDMA use (November Cover, p. 128)
• Modules combine control functions (November, p. 154)
• Compact plotter cuts prototype circuit boards (December, p. 258)
• Surface-mount diodes fit pads and switches (December, p. 260)

◀ MATERIALS ▶

• Materials offer low-cost option to FR-4 boards (January, p. 136)
• Circuit-board material promises thermal stability (February, p. 124)
• Characterizing conformal thin-film coatings from 200 to 1200 MHz (March, p. 116)
• Wafer bumping supports integration and reliability in ICs (March, p. 132)
• Jet process eases chip production (July, p. 148)
• Substrate materials support high-speed applications (July, p. 150)
• Tests characterize high-frequency material properties (August, p. 68)
• Making effective EM shields from aluminum and plastic (August, p. 128)
• Aluminum-nitride packages provide consistent performance (October, p. 156)

◀ SYSTEMS & SUBSYSTEMS ▶

• Low-cost SNA receiver measures across a 70-dB range (January, p. 77)
• Wireless telemetry system eases remote monitoring (February, p. 130)
• Processing methods enhance collision-warning systems (March,

p. 72)
• C-band transmitter module delivers 55-W output (March, p. 101)
• Test systems check for compliance with EM standards (March, p. 176)
• Compact satcom synthesizers cut current consumption (March, p. 182)
• Estimate IM in cellular-radio applications (April, p. 54)
• Interference cancellation improves GPS receiver performance (April, p. 62)
• Kit helps develop wireless data-communications systems (April, p. 129)
• Fiber-optic receiver handles digitally-modulated signals (April, p. 133)
• VSAT receiver assembly provides variable data rates (April, p. 136)
• Software suite helps manage process flow (April, p. 156)
• Burst-receiver assembly targets interactive CATV (May, p. 226)
• Dynamic parameters describe high-speed ADC performance (June, p. 81)
• Base station supports AMPS and TDMA systems (June, p. 148)
• Fiber-optic modules augment wireless systems (July, p. 142)
• Wireless systems move information at high speeds (August, p. 28)
• IR transceivers send data at 4 Mb/s (August, p. 201)
• GaAs ICs arm 10-Gb/s optical communications systems (September, p. 148)
• Active tuning system analyzes power transistors (October, p. 120)
• Portable system checks CDMA base stations (October Cover, p. 129)
• RF module combines three functions (November, p. 144)
• Speed up PLL switching to improve system performance (December, p. 153)
• Attain high bandwidth efficiency with VMSK modulation (December, p. 173)
• Low-cost 38-GHz radio links T1/E1 lines (December, p. 256)
• Programmable delay line controls wide range (December, p. 264)

◀ TEST & MEASUREMENT ▶

• Equipment tests wireless system performance (January, p. 29)
• Test facility aids UK's push for compliance (January, p. 39)
• Measure adjacent-channel power with a spectrum analyzer (January, p. 55)
• Test base-station antenna feedline systems (January, p. 95)
• Measurement method evaluates cable shielding effectiveness (January, p. 105)
• Probe cards test high-speed, multifunction ICs (January Cover, p. 113)
• Power meters offer flexible test capabilities (January, p. 134)
• Measurement group aims at calibration methods (February, p. 39)
• Vector analyzers combine speed with wide dynamic range (February, p. 142)
• Fully-synthesized analyzer is high-performance bargain (February, p. 148)
• Measuring the passive-IM performance of RF cable assemblies (March, p. 108)
• Use RMS detection and shaped probes for RF emission tests (March, p. 126)
• Test sets evaluate wireless performance parameters (March, p. 158)
• Color scopes recall 1-GHz bandwidths with long memories (March, p. 189)
• Spectrum analyzers scan wideband wireless signals (April, p. 110)
• PCS coverage test set speeds system mapping (April Cover, p. 120)
• System tests EMC compliance (April, p. 144)
• Single programmable instrument generates multiple signals (April, p. 146)
• Use network and spectrum analysis for mixer measurements, Part 1 (May, p. 143)
• Signal generators command complex modulation formats (May Cover, p. 195)
• Power meters add speed and power to test line (May, p. 209)
• Use network and spectrum analysis for mixer measurements, Part 2 (June, p. 71)
• Correcting misunderstandings on spectrum-analyzer RMS detection (June, p. 101)
• Versatile oscilloscope saves measurement time (June, p. 128)
• Digital oscilloscopes attack communications applications (June, p. 132)
• Cellular/PCS test set handles digital and analog standards (June, p. 138)
• Vector analyzers evolve for millimeter-wave testing (June, p. 152)
• Battery-powered counters read frequency and power (August, p. 188)
• Analyzers measure peak power up to 40 GHz (August, p. 194)
• Millimeter-wave VNAs extend to 110 GHz (August, p. 198)
• EM field probes work without spectrum analyzers (August, p. 200)
• Instrument offers highly-sensitive refractivity testing (September, p. 69)
• Understand spectrum analyzers' dynamic-range specifications (September, p. 86)
• Simple technique measures television line frequencies (September, p. 111)
• Novel signal-generation method enhances radio equipment testing (September, p. 117)
• Compute uncertainties for power-meter measurements (September, p. 128)
• Shedding light on fiber-optic testing (September, p. 141)
• Check optical data signals with an oscilloscope (September, p. 155)
• Perform device-life tests under RF conditions (October, p. 84)
• EMI test receiver evaluates 9 kHz to 2.75 GHz (October, p. 138)
• VXI spectrum analyzer scans signals to 8.5 GHz (October, p. 142)
• Microwave power meter adds potent options (October, p. 146)
• Spectrum analyzers tackle vector signals (November, p. 138)
• Sensor interface module enhances 400-MHz testing (November, p. 142)
• Multiport test set cuts reconnections (November, p. 158)
• Comprehending RF channel characteristics (December, p. 189)
• Portable antenna analyzer extends reach to 18 GHz (December Cover, p. 222)
• Spectrum analyzers measure to 40 GHz (December, p. 246)
• Multipath fading emulator aims at WCDMA (December, p. 254)